

DURAPLACER LIQUID60'/40' STRIP-TILL/STRIP FRESHENER

DuraPlacer Liquid utilizes Yetter Strip Freshener CC's to combine efficient strip-till or strip freshening with unmatched nutrient application productivity. DuraPlacer Liquid can be used for excellent seedbed preparation to warm the soil and improve planter ride or to build new strips on no-till ground.

DuraPlacer Liquid is offered both as a 24-row or 16-row toolbar on 30" rows and a 2400 gallon or 1800 gallon tank. Singles, Duals, and CAMSO™ Tracks are all available. The 24-row 2400 gallon toolbar is designed for application speeds of seven to ten mph to boost productivity with minimum 325 horsepower.



CONTACT FAST

WINDOM, MN

4130 Commerce Blvd, Windom, MN 56101 toll free 800-772-9279 | $\bf p$ 507-427-3861 | $\bf f$ 507-427-3030

GILMAN, IL

1340 S Crescent, PO Box 236, Gilman, IL 60938 toll free 800-872-8894 | **p** 815-265-7125 | **f** 815-265-7130

KEY FEATURES

- Can be used to make new strips in the Spring or Fall or freshen Fall-made strips while combining efficient nutrient application
- Front folding toolbar features narrow transport width of 15'3"
- Retractable tongue, along with outer flip wings on 60' toolbar to reduce length in the field
- Four independent flex hinges across the toolbar and adjustable hydraulic down pressure at each flex point
- Yetter Strip Freshener CC's In-Cab adjustable air pressure control on pneumatic row cleaners, rolling basket, and air downforce on the entire row unit

TOOLBAR FEATURES

- Four independent flex hinges across the toolbar and adjustable hydraulic down pressure at each flex point to ensure toolbar follows ground contours extremely well
 - ☐ Main Wings have 6 degrees up flex and 13 degrees down flex☐ Flip Wings have 9 degrees up and 8 degrees down
- Fold functions run through one hydraulic block/one remote on tractor
- Hydraulic WingKick standard to tilt outer wings up when toolbar is raised to increase ground clearance
- 5 Ball Valves/Plumbing Sections Standard







TRAILER FEATURES

- 2400 or 1800 Gallon patented Stealth Style Tank
 Low center of gravity, deep sump
- Singles, Duals, or CAMSO[™] Tracks all available
- Wide Stance Parallel Linkage to give stability to toolbar both in field position and while raised

YETTER STRIP-FRESHENER CC



- Build strips in the fall or spring, or utilize to refresh strips while placing liquid fertilizer
- Creates 10" wide strips, designed to accommodate the width of the planter unit for a better ride & consistent seed placement, improving emergence
- In-Cab Console Air Pressure Control on Row Unit
 - ☐ Adjustable air pressure on row cleaners to move residue for varying field conditions
- ☐ Adjustable air down pressure on row units
- ☐ Adjustable air cylinder pressure on rolling basket
- Parallel linkage for individual row performance
- Three-blade design for ideal mixture of soil
- Rolling basket for optimal soil conditioning



SPECS	DURAPLACER LIQUID
TRANSPORT WIDTH (FULLY ASSEMBLED)	15'3"
TRANSPORT WIDTH (SHIPPING)	11'6"
TRANSPORT HEIGHT	12'3" (60' TOOLBAR)
TOTAL LENGTH IN TRANSPORT	42'8"
TOTAL WEIGHT (EMPTY)	29,000 LBS
STANDARD PUMP	ACE 255-304 WET SEAL
QUICK FILL	3"
STANDARD TIRES	1800 GALLON - 480/80R50 SINGLES 2400 GALLON - 380/90R46 DUALS